

# N300

Capacity *1	16 TB	14 TB	12 TB	10 TB	8 TB	8 TB	6 TB	6 TB	4 TB
Drive model number	HDWG31G	HDWG21E	HDWG21C	HDWG11A	HDWG180	HDWN180	HDWG160	HDWN160	HDWQ140
<b>Basic Specifications</b>									
Interface *3	SATA 6.0 Gbit/s	SATA 6.0 Gbit/s	SATA 6.0 Gbit/s	SATA 6.0 Gbit/s	SATA 6.0 Gbit/s	SATA 6.0 Gbit/s	SATA 6.0 Gbit/s	SATA 6.0 Gbit/s	SATA 6.0 Gbit/s
Form Factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
Sector size	512e	512e	512e	512e	512e	512e	512e	512e	512n
<b>Features</b>									
Drive Bays Supported *2	8	8	8	8	8	8	8	8	8
24 x 7 Operation (Workloads [TB/year] *4)	180	180	180	180	180	180	180	180	180
<b>Performances</b>									
Rotation Speed [rpm]	7,200	7,200	7,200	7,200	7,200	7,200	7,200	7,200	7,200
Max Data Transfer Speed [MB/s Typ.][Sustained] *3	274	260	253	248	241	241	241	241	204
Buffer Size [MB]	512	256	256	256	256	128	256	128	128
<b>Reliability</b>									
MTTF [hours] *5	1,200,000	1,000,000	1,000,000	1,000,000	1,000,000	1,000,000	1,000,000	1,000,000	1,000,000
Unrecoverable Error Rate	1 per 10 <sup>14</sup>	1 per 10 <sup>14</sup>	1 per 10 <sup>14</sup>	1 per 10 <sup>14</sup>	1 per 10 <sup>14</sup>	1 per 10 <sup>14</sup>	1 per 10 <sup>14</sup>	1 per 10 <sup>14</sup>	1 per 10 <sup>14</sup>
Load/Unload cycles	300,000	300,000	300,000	300,000	300,000	300,000	300,000	300,000	300,000
<b>Power Requirements</b>									
Supply Voltage	5 V DC +10 % / -7 % 12 V DC ±10 %	5 V DC ±5 % 12 V DC ±10 %	5 V DC ±5 % 12 V DC ±10 %	5 V DC +10 / -5 % 12 V DC ±10 %	5 V DC +10 / -5 % 12 V DC ±10 %	5 V DC ±5 % 12 V DC ±10 %	5 V DC +10 / -5 % 12 V DC ±10 %	5 V DC ±5 % 12 V DC ±10 %	5 V DC ±5 % 12 V DC ±10 %
Power Consumption (Spin up (+12V DC)) [A] *6	1.47	1.65	1.62	1.44	1.43	1.83	1.44	1.88	1.84
Power Consumption (Operating) [W] *7	6.91	6.77	6.49	9.92	8.61	9.20	7.88	10.1	9.6
Power Consumption (Active Idle) [W]	4.03	4.54	4.28	7.22	6.33	6.20	5.59	6.7	5.2
<b>Dimensions</b>									
Height [mm Max.]	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1	26.1
Length [mm Max.]	147.0	147.0	147.0	147.0	147.0	147.0	147.0	147.0	147.0
Width [mm Max.]	101.85	101.85	101.85	101.85	101.85	101.85	101.85	101.85	101.85
Weight [g Max.]	720	720	720	770	770	770	770	770	720
Bottom holes type *8	TYPE1	TYPE1	TYPE1	TYPE1	TYPE1	TYPE1	TYPE1	TYPE1	TYPE2
<b>Environmental Requirements</b>									
Temperature ( Operating ) [ °C ]	5 to 65 (surface)	5 to 60 (surface)	5 to 60 (surface)	0 to 65 (surface)	0 to 65 (surface)	0 to 65 (surface)	0 to 65 (surface)	0 to 65 (surface)	0 to 65 (surface)
Temperature ( Non-operating ) [ °C ]	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70
Vibration ( Operating )	7.35 m/s <sup>2</sup> (0.75G) (5 to 300Hz) 2.45 m/s <sup>2</sup> (0.25G) (300 to 500Hz)	7.35 m/s <sup>2</sup> (0.75G) (5 to 300Hz) 2.45 m/s <sup>2</sup> (0.25G) (300 to 500Hz)	7.35 m/s <sup>2</sup> (0.75G) (5 to 300Hz) 2.45 m/s <sup>2</sup> (0.25G) (300 to 500Hz)	7.35 m/s <sup>2</sup> (0.75G) (5 to 300Hz) 2.45 m/s <sup>2</sup> (0.25G) (300 to 500Hz)	7.35 m/s <sup>2</sup> (0.75G) (5 to 300Hz) 2.45 m/s <sup>2</sup> (0.25G) (300 to 500Hz)	7.35 m/s <sup>2</sup> (0.75G) (5 to 300Hz) 2.45 m/s <sup>2</sup> (0.25G) (300 to 500Hz)	7.35 m/s <sup>2</sup> (0.75G) (5 to 300Hz) 2.45 m/s <sup>2</sup> (0.25G) (300 to 500Hz)	7.35 m/s <sup>2</sup> (0.75G) (5 to 300Hz) 2.45 m/s <sup>2</sup> (0.25G) (300 to 500Hz)	7.35 m/s <sup>2</sup> (0.75G) (5 to 300Hz) 2.45 m/s <sup>2</sup> (0.25G) (300 to 500Hz)
Vibration ( Non-operating )	29.4 m/s <sup>2</sup> (3.0G) (5 to 500Hz)	29.4 m/s <sup>2</sup> (3.0G) (5 to 500Hz)	29.4 m/s <sup>2</sup> (3.0G) (5 to 500Hz)	29.4 m/s <sup>2</sup> (3.0G) (5 to 500Hz)	29.4 m/s <sup>2</sup> (3.0G) (5 to 500Hz)	29.4 m/s <sup>2</sup> (3.0G) (5 to 500Hz)	49.0 m/s <sup>2</sup> (5G) (5 to 500 Hz )	29.4 m/s <sup>2</sup> (3.0G) (5 to 500Hz)	49.0 m/s <sup>2</sup> (5G) (5 to 500 Hz )
Shock ( Operating )	686 m/s <sup>2</sup> (70G) (2 ms duration)	686 m/s <sup>2</sup> (70G) (2 ms duration)	686 m/s <sup>2</sup> (70G) (2 ms duration)	686 m/s <sup>2</sup> (70G) (2 ms duration)	686 m/s <sup>2</sup> (70G) (2 ms duration)	686 m/s <sup>2</sup> (70G) (2 ms duration)	686 m/s <sup>2</sup> (70G) (2 ms duration)	686 m/s <sup>2</sup> (70G) (2 ms duration)	686 m/s <sup>2</sup> (70G) (2 ms duration)
Shock ( Non-operating )	2,450 m/s <sup>2</sup> (250G) (2 ms duration)	2,450 m/s <sup>2</sup> (250G) (2 ms duration)	2,450 m/s <sup>2</sup> (250G) (2 ms duration)	2,450 m/s <sup>2</sup> (250G) (2 ms duration)	2,450 m/s <sup>2</sup> (250G) (2 ms duration)	2,450 m/s <sup>2</sup> (250G) (2 ms duration)	2,450 m/s <sup>2</sup> (250G) (2 ms duration)	2,450 m/s <sup>2</sup> (250G) (2 ms duration)	2,450 m/s <sup>2</sup> (250G) (2 ms duration)
Acoustics(Sound Power) Idle mode [dB]	20	20	20	34	34	33	34	33	30

\*1: One Gigabyte (1GB) means 10<sup>9</sup> = 1,000,000,000 bytes and One Terabyte (1TB) means 10<sup>12</sup> = 1,000,000,000,000 bytes using powers of 10. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1GB = 2<sup>30</sup> = 1,073,741,824 bytes and 1TB = 2<sup>40</sup> = 1,099,511,627,776 bytes, and therefore shows less storage capacity. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system and other factors.

\*2: As for "Drive Bays Supported", please contact your Solutions Provider because the compatibility with the host device will vary based on the system.

\*3: Read and write speed may vary depending on the host device, read and write conditions, and file size.

\*4: Workload is defined as the amount of data written, read or verified by commands from host system.

\*5: MTTF (Mean Time to Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products

which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF.

\*6: Not including glitch less than 100 μs.

\*7: Operating watt is measured using 80% random read/write and 20% performance idle.

\*8: Location of bottom mounting hole is different from product. For more information, please see the following page.